

HUMLOG 10

Humidity / Temperature Data Logger

HUMLOG 10 series humidity/temperature data loggers permit the exact and professional recording of humidity and temperature values. Low power consumption and large memory size enable long-term data capture for a wide range of applications. The HUMLOG 10 can be configured very easily by means of the included software. Alarm thresholds for humidity and temperature, as well as the start time for recording, can be freely set by the user.

The 3 available HUMLOG 10 models allow optimum adaptation to any requirements.

HUMLOG 10 / HUMLOG 10TSE

The elegant 2-part housing, which consists of a display module and a plug-in sensor module, enables easy installation and a fast exchange of the sensor unit when service is required.

The current measurement data on the large display is easy to read even from a distance of several metres. Relative humidity (% RH) and temperature (°C or °F) are constantly displayed. Clock time (format hh:mm) and date (format dd.mm) are displayed in an alternating sequence. Likewise, the display also indicates alarm conditions, recording, record stop, and programmed record start.

In the basic version of the HUMLOG 10, the sensors are integrated in the sensor module. The HUMLOG 10TSE version is equipped for the connection of sensing probes. According to requirements, the two channels can be selectively connected to a combination H/T sensing probe or to 2 T sensing probes. The sensing probes can be separated; maximum distance: 8 m. The optional Professional Version of the Smartgraph™2 software enables the control of 2 combined H/T sensing probes.


HUMLOG 10THC

The compact HUMLOG 10THC version does not have a display and is equipped with internal H/T sensors.

Measurement Data - Evaluation & Configuration

Measurement data evaluation and instrument configuration can be conveniently performed via the serial RS232 interface with a PC or notebook computer by means of the Smartgraph™2 software, which runs under MS Windows™.

Smartgraph™2 can display the recorded measurement data in graphical form or as a table. The layout of the display can be individually configured by the user.



The optional Professional Version of Smartgraph™2 also permits the display of dewpoint and absolute humidity, the export of measured values (e.g., for evaluation by means of MS Excel™), and the control of 2 combined H/T sensing probes.

HUMLOG 10



HUMLOG 10TSE with RH/T probe



HUMLOG 10TSE with 2 T probes



HUMLOG 10THC





INGENIEROS ASOCIADOS DE CONTROL S.L.

Tel.: 913831390
comercial@iac-si.es

Typical Applications

museums and exhibition spaces
clean rooms
green houses
warehouses

Features

data memory for 120,000 values
large format display
easy installation and service
user friendly data evaluation via PC-software

Technical Data

	HUMLOG 10TSE	HUMLOG 10 / HUMLOG 10THC
Sensing probe		
Model	external RH/T or T	internal RH/T
Dimensions	RH/T-probe: length 80mm, Ø14mm T-probe: length 50mm, Ø6mm	
Max. cable length	8m	
Measuring data		
Relative humidity		RH/T probe external
Sensor type	capacitive - HC1000	capacitive - HC103
Measuring range	0...100% RH (non condensing)	10...95% RH
Accuracy	±2% RH	±3% RH
Resolution	0.5% RH	0.5% RH
Temperature		RH/T probe internal
Sensor type	NTC	NTC
Measuring range	-30...70 degC	-20...50 degC
Accuracy	±0.2 degC at -20...50 degC otherwise 0.5 deg	±0.3 degC at 0...40 degC otherwise ±0.5 degC
Resolution	0.1 degC	0.1 degC
Temperatur		T probe external
Sensor type	NTC	
Measuring range	-40...100 degC	
Accuracy	±0.2 degC (-20...50 degC) ±0.4 degC (-40...70 degC) ±1.0 degC (>70 degC)	
Resolution	0.1°C	

General

Supply voltage	3.6V lithium battery		
Battery lifetime	typical 2 years (with a sample rate of 1min)		
Internal memory size	60,000 measured values/channel (total 120,000 values)		
Sampling interval	1/10/30sec, 1/10/30min, 1/3/6/12/24h		
Logging interval	1/10/30min, 1/3/6/12/24h		
Serial Interface	RS232		
Working temperature range	housing: -20...50°C		
CE compatibility according	EN50081-2	EN50082-2	EN55011
	EN61000-4-2	EN61000-4-3	
Housing / protection class	ABS / IP40		
Dimensions (WxHxD)	120x110x30mm	resp. HUMLOG 10THC: 120x50x30mm	
Weight	250g	resp. HUMLOG 10THC: 90g	
Display	LCD, 65x40mm	(only HUMLOG 10 / HUMLOG 10TSE)	



Scope of Supply

HUMLOG 10, RS232 interface cable, 3.6V lithium battery, operation manual
SmartGraph™2 PC-Windows™-Software for set-up and data presentation,

Ordering Guide

MODEL	EXTERNAL PROBE (for HUMLOG 10TSE)	ACCESSORIES
with internal sensors and display	(HUMLOG 10)	SmartGraph™2 Professional (HA 03 01 01)
for external probes, with display	(HUMLOG 10TSE)	3.6V lithium battery (HA 03 01 02)
with internal sensors, without display	(HUMLOG 10THC)	sensing module (HA 03 01 03)
	RH/T - probe with 2m cable (HA 03 02 01)	theft-proof installation kit (HA 03 01 04)
	T - probe with 2m cable (HA 03 02 02)	
	cable extension 2m (HA 03 02 03)	

HUMLOG 10